

| Technical data | | |
|--|-------------------------------|-----------------------|
| Weight | 900 kg | 1,984 lbs |
| Diesel engine (4 cylinders) | 19 kW | 25.5 hp |
| Compressor | 4 cylinders / Open compressor | |
| Electric motor | 11 kW | 14.8 hp |
| Refrigerant | R452A / 8.0 kg | |
| Applications | | |
| FRC max | 15.0 m | 49 ft |
| FNA max | over 20.0 m | over 66 ft |
| Cooling capacity at an outdoor temperature of +30 °C (86°F) | | |
| Transportation temperature | 0°C (32°F) | -20°C (-4°F) |
| In diesel mode | 14.9 kW (50,900 BTU/h) | 7.8 kW (26,700 BTU/h) |
| In electric mode | 9.5 kW (32,300 BTU/h) | 7.6 kW (26,000 BTU/h) |
| Heating capacity at an outdoor temperature of -20 °C (-4°F) | | |
| In diesel mode | 10.1 kW | 34,500 BTU/h |
| In electric mode | 10.1 kW | 34,500 BTU/h |
| Fan power | | |
| Evaporator air volume | 4,800 m ³ /h | 2,825 CFM |
| Air exit speed | 18.0 m/s | 40.3 mph |